

AMENDMENT A, Contd.

CLAIMS

What is claimed is:

Claims 1-109 (cancelled)

110. (new): A network having a plurality of multicast connections, said network
- 5 comprising:
- an input stage comprising r_1 input switches, and n_1 inlet links for each of said r_1 input switches;
- an output stage comprising r_2 output switches, and n_2 outlet links for each of said r_2 output switches; and
- 10 a middle stage comprising m middle switches, and each middle switch comprising at least one link (hereinafter "first internal link") connected to each input switch for a total of at least r_1 first internal links, each middle switch further comprising at least one link (hereinafter "second internal link") connected to each output switch for a total of at least r_2 second internal links;
- 15 said network further is always capable of setting up said multicast connection by never changing path of an existing multicast connection, and the network is hereinafter
- 20 "strictly nonblocking network", where m is a minimum of at least $2 * n_1 + n_2 - 1$.

B10

C1 1+2

111. (new): The network of claim 110 wherein each multicast connection from an inlet link passes through at most two middle switches, and said multicast connection further
- 20 passes to a plurality of outlet links from said at most two middle switches.
112. (new): The network of claim 110 further comprising a controller coupled to each of said input, output and middle stages to set up said multicast connection.
113. (new): The network of claim 110 wherein said r_1 input switches and r_2 output switches are the same number of switches.

AMENDMENT A, Contd.

114. (new): The network of claim 110 wherein said n_1 inlet links and n_2 outlet links are the same number of links and $n_1 = n_2 = n$, then m is a minimum of at least $3 * n - 1$.
115. (new): The network of claim 110,
wherein each of said input switches, or each of said output switches, or each of
5 said middle switches further recursively comprise one or more networks.
116. (new): A method for setting up one or more multicast connections in a network
having an input stage having $n_1 * r_1$ inlet links and r_1 input switches, an output stage
having $n_2 * r_2$ outlet links and r_2 output switches, and a middle stage having m middle
switches, where each middle switch is connected to each of said r_1 input switches through
10 r_1 first internal links and each middle switch further comprising at least one link
connected to at most d said output switches for a total of at least d second internal links,
wherein $1 \leq d \leq r_2$, said method comprising:
receiving a multicast connection at said input stage;
fanning out said multicast connection in said input stage into at most two middle
15 switches to set up said multicast connection to a plurality of output switches among said
 r_2 output switches, wherein said plurality of output switches are specified as destinations
of said multicast connection, wherein first internal links from said input switch to said at
most two middle switches and second internal links to said destinations from said at most
two middle switches are available;
20 wherein said act of fanning out is performed without changing any existing
connection to pass through another middle switch.
117. (new): The method of claim 116 wherein said act of fanning out is performed
recursively.
118. (new): A method for setting up one or more multicast connections in a network
25 having an input stage having $n_1 * r_1$ inlet links and r_1 input switches, an output stage
having $n_2 * r_2$ outlet links and r_2 output switches, and a middle stage having m middle
switches, where each middle switch is connected to each of said r_1 input switches through

AMENDMENT A, Contd.

r_1 first internal links and each middle switch further comprising at least one link connected to at most d said output switches for a total of at least d second internal links, wherein $1 \leq d \leq r_2$, said method comprising:

checking if at least a first subset of destination output switches of said multicast
5 connection have available second internal links to a first middle switch; and
checking if a second middle switch has available second internal links to a second subset of destination output switches of said multicast connection.

wherein each destination output switch of said multicast connection is one of said first subset of destination output switches and said second subset of destination output
10 switches.

119. (new): The method of claim 118 further comprising:

checking if the input switch of said multicast connection has an available first internal link to said first middle switch and to said second middle switch.

120. (new): The method of claim 118 further comprising:

15 prior to said checkings, checking if all the destination output switches of said multicast connection are available at said first middle switch.

121. (new): The method of claim 118 further comprising:

repeating said checkings of available second internal links to another second subset of destination output switches for each middle switch other than said first and said
20 second middle switches.

wherein each destination output switch of said multicast connection is one of said first subset of destination output switches and said second subset of destination output switches.

122. (new): The method of claim 118 further comprising:

25 repeating said checkings of available second internal links to another first subset of destination output switches with each middle stage switch other than said first middle stage switch.

123. (new): The method of claim 118 further comprising:

AMENDMENT A, Contd.

repeating said checkings of ~~available~~ first internal link to each middle stage switch other than said first middle switch and said second middle switch.

124. (new): The method of claim 118 further comprising:

5 setting up each of said multicast connection from its said input switch to its said output switches through not more than two middle switches, selected by said checkings, by fanning out said multicast connection in its said input switch into not more than said two middle stage switches.

125. (new): The method of claim 118 wherein any of said acts of checking and setting up are performed recursively.

10 126. (new): A method of setting up a multicast connection through a three-stage network, said method comprising:

19+20
B10
15 fanning out only one or two times in an initial stage,
 and fanning out any number of times in each of the remaining stages,
 wherein said three-stage network includes said remaining stages and said initial stage.

127. (new): The method of claim 126 further comprising:

 repeating said acts of fanning out with a plurality of portions of each of said stages.

128. (new): The method of claim 126 further comprising:

20 recursively performing said act of fanning out.

129. (new): The method of claim 126 wherein:

 a remaining stage immediately following said initial stage comprises internal links that are at least two times the total number of inlet links of said initial stage.

130. (new): The method of claim 126 wherein:

25 said initial stage comprises a plurality of first switches, and a plurality of inlet links connected to each said first switch; and

AMENDMENT A, Contd.

a remaining stage immediately following said initial stage comprises a plurality of second switches, that are at least double the number of inlet links of each first switch and each second switch comprises a plurality of internal links at least equal in number to the number of first switches in said initial stage.

- 5 131. (new): A network having a plurality of multicast connections, said network comprising:

an input stage comprising r_1 input switches and n_1 inlet links for each of said r_1 input switches, and $N_1 = n_1 * r_1$;

- an output stage comprising r_2 output switches and n_2 outlet links for each of said
10 r_2 output switches, and $N_2 = n_2 * r_2$; and

a middle stage comprising m middle switches, and each middle switch comprising at least one link connected to each input switch for a total of at least r_1 first internal links; each middle switch further comprising at least one link connected to each output switch for a total of at least r_2 second internal links,

- 15 said network further is always capable of setting up said multicast connection by never changing path of an existing multicast connection, and the network is hereinafter "strictly nonblocking network", where m is a minimum of at least $3 * n_1 + n_2 - 1$.

132. (new): The network of claim 131 wherein each multicast connection from an inlet link passes through at most three middle switches, and said multicast connection further
20 passes to a plurality of outlet links from said at most three middle switches.

133. (new): The network of claim 131 comprising a controller in communication with said input, output and middle stages to set up said multicast connection.

134. (new): The network of claim 131 wherein said r_1 input switches and r_2 output switches are the same number of switches.

- 25 135. (new): The network of claim 131 wherein said n_1 inlet links and n_2 outlet links are the same number of links and $n_1 = n_2 = n$, then m is a minimum of at least $4 * n - 1$.

AMENDMENT A, Contd.

136. (new): The network of claim 131,

wherein each of said input switches, or each of said output switches, or each of said middle switches further recursively comprise one or more networks.

137. (new): A method for setting up one or more multicast connections in a network

- 5 having an input stage having $n_1 * r_1$ inlet links and r_1 input switches, an output stage having $n_2 * r_2$ outlet links and r_2 output switches, and a middle stage having m middle switches, where each middle switch is connected to each of said r_1 input switches through r_1 first internal links and each middle switch further comprising at least one link connected to at most d said output switches for a total of at least d second internal links,
- 10 wherein $1 \leq d \leq r_2$, said method comprising :

receiving a multicast connection at said input stage;

fanning out said multicast connection in said input stage into at most three middle switches to set up said multicast connection to a plurality of output switches among said r_2 output switches of said multicast connection, wherein said plurality of output switches

15 are specified as destinations of said multicast connection, wherein first internal links from said input switch to said at most three middle switches and second internal links to said destinations from said at most three middle switches are available,

wherein said act of fanning out is performed without changing any existing connection to pass through another middle switch.

- 20 138. (new): The method of claim 137 wherein said act of fanning out is performed recursively.

139. (new): A method for setting up one or more multicast connections in a network

having an input stage having $n_1 * r_1$ inlet links and r_1 input switches, an output stage having $n_2 * r_2$ outlet links and r_2 output switches, and a middle stage having m middle switches, where each middle switch is connected to each of said r_1 input switches through r_1 first internal links and each middle switch further comprising at least one link

25

AMENDMENT A, Contd.

connected to at most d said output switches for a total of at least d second internal links, wherein $1 \leq d \leq r_2$, said method comprising:

checking if all the destination output switches of said multicast connection have available second internal links from at most three middle switches.

5 140. (new): The method of claim 139 further comprising:

checking if the input switch of said multicast connection has available first internal links to at most said three middle switches.

141. (new): The method of claim 139 further comprising:

10 repeating said checkings of available second internal links to all said destination output switches for all the other combinations of at most three middle switches.

142. (new): The method of claim 139 further comprising:

repeating said checkings of available first internal links for all the other combinations of at most three middle switches.

143. (new): The method of claim 139 further comprising:

15 setting up each of said connection from its said input switch to its said output switches through at most said three middle switches, selected by said checkings, by fanning out said multicast connection in its said input switch into at most said three middle stage switches;

144. (new): The method of claim 139 wherein any of said acts of checking and setting up
20 are performed recursively.

145. (new): A method of setting up a multicast connection through a three-stage network, said method comprising:

fanning out at most three times in an initial stage,

and fanning out any number of times in each of the remaining stages,

25 wherein said three-stage network includes said remaining stages and said initial stage.

AMENDMENT A, Contd.

146. (new): The method of claim 145 further comprising:
repeating said acts of fanning out with a plurality of portions of each said stages.

147. (new): The method of claim 145 further comprising:
recursively performing said act of fanning out.

5 148. (new): The method of claim 145 wherein:
a remaining stage immediately following said initial stage comprises internal links
that are at least three times the total number of inlet links of said initial stage.

149. (new): The method of claim 145 wherein:
said initial stage comprises a plurality of first switches, and plurality of inlet links
10 connected to each said first switch; and
a remaining stage immediately following said initial stage comprises a plurality of
second switches, that are at least three times the number of inlet links of each first switch
and each second switch comprises a plurality of first internal links at least equal in
number to the number of first switches in said initial stage.
15 said multicast connections having a fan-out of one or more in said middle stage.

150. (new): A network having a plurality of multicast connections, said network
comprising:

an input stage comprising r_1 input switches and n_1 inlet links for each of said r_1
input switches, and $N_1 = n_1 * r_1$;

20 an output stage comprising r_2 output switches and n_2 outlet links for each of said
 r_2 output switches, and $N_2 = n_2 * r_2$; and

a middle stage comprising m middle switches, and each middle switch
comprising at least one link connected to each input switch for a total of at least r_1 first
internal links; each middle switch further comprising at least one link connected to each
25 output switch for a total of at least r_2 second internal links, for $x \geq 1$,

AMENDMENT A, Contd.

said network further is always capable of setting up said connection by never changing path of a previously set up multicast connection, and the network is hereinafter "strictly nonblocking network", where $m \geq x * n_1 + n_2 - 1$, for $x \geq 2$.

151. (new): The network of claim 150 wherein each multicast connection from an inlet
5 link passes through at most x middle switches, and said multicast connection further passes to a plurality of outlet links from said at most x middle switches.

152. (new): The network of claim 150 comprising a controller in communication with said input, output and middle stages to set up said multicast connection.

153. (new): The network of claim 150 wherein said r_1 input switches and r_2 output
10 switches are the same number of switches.

154. (new): The network of claim 150 wherein said n_1 inlet links and n_2 outlet links are the same number of links and $n_1 = n_2 = n$, then $m \geq (x+1)*n - 1$.

B10
155. (new): The network of claim 150,
wherein each of said input switches, or each of said output switches, or each of
15 said middle switches further recursively comprise one or more networks.

156. (new): A method for setting up one or more multicast connections in a network having an input stage having $n_1 * r_1$ inlet links and r_1 input switches, an output stage having $n_2 * r_2$ outlet links and r_2 output switches, and a middle stage having m middle switches, where each middle switch is connected to each of said r_1 input switches through
20 r_1 first internal links and each middle switch further comprising at least one link connected to at most d said output switches for a total of at least d second internal links, wherein $1 \leq d \leq r_2$, for $x \geq 2$, said method comprising:

61+62
receiving a multicast connection at said input stage;
fanning out said multicast connection in said input stage into at most x middle
25 switches to set up said multicast connection to a plurality of output switches among said

AMENDMENT A, Contd.

r_2 output switches, wherein said plurality of output switches are specified as destinations of said multicast connection, wherein first internal links from said input switch to said at most x middle switches and second internal links to said destinations from said at most x middle switches are available,

- 5 wherein said act of fanning out is performed without changing any existing connection to pass through another middle switch.

157. (new): The method of claim 156 wherein said act of fanning out is performed recursively.

158. (new): A method for setting up one or more multicast connections in a network
10 having an input stage having $n_1 * r_1$ inlet links and r_1 input switches, an output stage having $n_2 * r_2$ outlet links and r_2 output switches, and a middle stage having m middle switches, where each middle switch is connected to each of said r_1 input switches through r_1 first internal links and each of said r_2 said output switches through r_2 second internal links, for $x \geq 2$, said method comprising:

- 15 checking if all the destination output switches of said multicast connection have available second internal links from at most x middle switches.

159. (new): The method of claim 158 further comprising:

 checking if the input switch of said multicast connection has an available first internal links to said at most x middle switches.

- 20 160. (new): The method of claim 158 further comprising:

 repeating said checkings of available second internal links to all said destination output switches for all the other combinations of at most x middle switches.

161. (new): The method of claim 158 further comprising:

- 25 repeating said checkings of available first internal links for all the other combinations of at most x middle switches.

162. (new): The method of claim 158 further comprising:

AMENDMENT A, Contd.

setting up each of said connection from its said input switch to its said output switches through at most x said middle switches, selected by said checkings, by fanning out said multicast connection in its said input switch into at most said x middle stage switches.

- 5 163. (new): The method of claim 158 wherein any of said acts of checking and setting up are performed recursively.

164. (new): A method of setting up a multicast connection through a three-stage network, for $x \geq 2$, said method comprising:

- 10 fanning out at most x times in an initial stage,
and fanning out any number of times in each of the remaining stages,
wherein said three-stage network includes said remaining stages and said initial stage.

165. (new): The method of claim 164 further comprising:

- 15 repeating said acts of fanning out with a plurality of portions of each of said stages.

166. (new): The method of claim 164 further comprising:

recursively performing said act of fanning out.

167. (new): The method of claim 164 wherein:

- 20 a remaining stage immediately following said initial stage comprises internal links that are at least x times the total number of inlet links of said initial stage.

168. (new): The method of claim 164 wherein:

said initial stage comprises a plurality of first switches, and plurality of inlet links connected to each said first switch; and

- 25 a remaining stage immediately following said initial stage comprises a plurality of second switches that are at least x times the number of inlet links of each first switch and each second switch comprises a plurality of first internal links at least equal in number to the number of first switches in said initial stage.

AMENDMENT A, Contd.

169. (new): A network having a plurality of multicast connections, said network comprising:

an input stage comprising r_1 input switches and n_1 inlet links for each of said r_1 input switches, and $N_1 = n_1 * r_1$;

5 an output stage comprising r_2 output switches and n_2 outlet links for each of said r_2 output switches, and $N_2 = n_2 * r_2$; and

a middle stage comprising m middle switches, and each middle switch comprising at least one link connected to each input switch for a total of at least r_1 first internal links; each middle switch further comprising at least one link connected to at most d said output switches for a total of at least d second internal links, wherein
10 $1 \leq d \leq r_2$,

wherein $m \geq \sum_{i=1}^p (x_i * a_i + n_1 - 1)$, where $\sum_{i=1}^p a_i = n_1 + n_2$ and $x_1, x_2, \dots, x_p \geq 1$;

wherein, for $1 \leq i \leq p$, multicast connections from a_i inlet links of each input switch pass through at most x_i middle switches,

15 said network further is capable of setting up said connection by never changing path of a previously set up multicast connection, and the network is hereinafter "strictly nonblocking network", where $x_1, x_2, \dots, x_p \geq 2$.

170. (new): The network of claim 169 comprising a controller in communication with said input, output and middle stages to set up said multicast connection.

20 171. (new): The network of claim 169 wherein said r_1 input switches and r_2 output switches are the same number of switches.

172. (new): The network of claim 169 wherein said n_1 inlet links and n_2 outlet links are the same number of links and $n_1 = n_2 = n$.

173. (new): The network of claim 169,

AMENDMENT A, Contd.

wherein each of said input switches, or each of said output switches, or each of said middle switches further recursively comprise one or more networks.

174. (new): A network having a plurality of multicast connections, said network comprising:

- 5 an input stage comprising r_1 input switches and n_1 inlet links for each of said r_1 input switches, and $N_1 = n_1 * r_1$;
- an output stage comprising r_2 output switches and n_2 outlet links for each of said r_2 output switches, and $N_2 = n_2 * r_2$; and
- a middle stage comprising m middle switches, and each middle switch
- 10 comprising at least one link connected to each input switch for a total of at least r_1 first internal links; each middle switch further comprising at least one link connected to at most d said output switches for a total of at least d second internal links, wherein $1 \leq d \leq r_2$,

- said network further is always capable of setting up said connection by never
- 15 changing path of a previously set up multicast connection, and the network is hereinafter "strictly nonblocking network", where m is a minimum of at least $2 * n_1 + n_2 - 1$.

175. (new): The network of claim 174 wherein each multicast connection from an inlet link passes through at most one or two middle switches, and said multicast connection further passes a plurality of outlet links from said at most two middle switches.

- 20 176. (new): The network of claim 174 comprising a controller in communication with said input, output and middle stages to set up said multicast connection.

177. (new): The network of claim 174 wherein said r_1 input switches and r_2 output switches are the same number of switches.

178. (new): The network of claim 174 wherein said n_1 inlet links and n_2 outlet links are
- 25 the same number of links and $n_1 = n_2 = n$, then m is a minimum of at least $3 * n - 1$.

AMENDMENT A, Contd.

179. (new): The network of claim 174,
wherein each of said input switches, or each of said output switches, or each of
said middle switches further recursively comprise one or more networks.

180. (new): A network having a plurality of multicast connections, said network
5 comprising:

an input stage comprising r_1 input switches and n_1 inlet links for each of said r_1
input switches, and $N_1 = n_1 * r_1$;

an output stage comprising r_2 output switches and n_2 outlet links for each of said
 r_2 output switches, and $N_2 = n_2 * r_2$; and

93+94+95 10 a middle stage comprising m middle switches, and each middle switch
comprising at least one link connected to each input switch for a total of at least r_1 first
internal links; each middle switch further comprising at least one link connected to at
most d said output switches for a total of at least d second internal links, wherein
 $1 \leq d \leq r_2$,

B10 15 said network further is always capable of setting up said connection by never
changing path of a previously set up multicast connection, and the network is hereinafter
"strictly nonblocking network", where m is a minimum of at least $3 * n_1 + n_2 - 1$.

181. (new): The network of claim 180 wherein each multicast connection from an inlet
link passes through at most three middle switches, and said multicast connection further
20 passes a plurality of outlet links from said at most three middle switches.

182. (new): The network of claim 180 comprising a controller in communication with
said input, output and middle stages to set up said multicast connection.

183. (new): The network of claim 180 wherein said r_1 input switches and r_2 output
switches are the same number of switches.

25 184. (new): The network of claim 180 wherein said n_1 inlet links and n_2 outlet links are
the same number of links and $n_1 = n_2 = n$, then m is a minimum of at least $4 * n - 1$.

AMENDMENT A, Contd.

185. (new): The network of claim 180 ,
wherein each of said input switches, or each of said output switches, or each of
said middle switches further recursively comprise one or more networks.

186. (new): A network having a plurality of multicast connections, said network
5 comprising:

an input stage comprising r_1 input switches and n_1 inlet links for each of said r_1
input switches, and $N_1 = n_1 * r_1$;

an output stage comprising r_2 output switches and n_2 outlet links for each of said
 r_2 output switches, and $N_2 = n_2 * r_2$; and

10 a middle stage comprising m middle switches, and each middle switch
comprising at least one link connected to each input switch for a total of at least r_1 first
internal links; each middle switch further comprising at least one link connected to at
most d output switches for a total of at least d second internal links, wherein $1 \leq d \leq r_2$,
for $2 \leq x \leq r_2$,

15 said network further is always capable of setting up said connection by never
changing path of a previously set up multicast connection, and the network is hereinafter
"strictly nonblocking network", where $m \geq x * n_1 + n_2 - 1$.

187. (new): The network of claim 186 wherein each multicast connection from an inlet
link passes through at most x middle switches, and said multicast connection further
20 passes a plurality of outlet links from said at most x middle switches.

188. (new): The network of claim 186 comprising a controller in communication with
said input, output and middle stages to set up said multicast connection.

189. (new): The network of claim 186 wherein said r_1 input switches and r_2 output
switches are the same number of switches.

25 190. (new): The network of claim 186 wherein said n_1 inlet links and n_2 outlet links are
the same number of links and $n_1 = n_2 = n$, then $m \geq (x + 1) * n$.

AMENDMENT A, Contd.

191. (new): The network of claim 186,
wherein each of said input switches, or each of said output switches, or each of
said middle switches further recursively comprise one or more networks.

192. (new): A network comprising a plurality of input subnetworks, a plurality of middle
5 subnetworks, and a plurality of output subnetworks, wherein at least one of said input
subnetworks, said middle subnetworks and said output subnetworks recursively comprise:

an input stage comprising r_1 input switches and n_1 inlet links for each of said r_1
input switches;

an output stage comprising r_2 output switches and n_2 outlet links for each of said
10 r_2 output switches; and

a middle stage, said middle stage comprising m middle switches, and each middle
switch comprising at least one link (hereinafter "first internal link") connected to each
input switch for a total of at least r_1 first internal links, each middle switch further
comprising at least one link (hereinafter "second internal link") connected to at most d
15 said output switches for a total of at least d second internal links, wherein $1 \leq d \leq r_2$,
and for $x \leq 2$;

wherein each multicast connection from an inlet link passes through at most x
middle switches, and said multicast connection further passes to a plurality of outlet links
from said at most x middle switches.

AMENDMENT A, Contd.

Table 1 below shows the correspondence of the Claims between the current patent application and Amendment A.

Table 1 Correspondence of Claims between the patent application 09/967106 and Amendment A

09/967,106	AMENDMENT A	09/967,106	AMENDMENT A
1	110		142 added
2-3	Merged with 110	42-43	143-144
	111 (separated from 110)	44	145
4-6	112-114	45	Merged with 145
7	Deleted	46-49	146-149
8	115	50-52	Deleted
9	116	53	150
10	Merged into 116	54-55	Merged with 150
11	117		151 (separated from 150)
✓ 12-16	118-122	56-58	152-154
	123 added	59	Deleted
17-18	124-125	60	155
19	126	61	156
20	Merged with 126	62	Merged into 156
21-24	127-130	63	157
25-27	Deleted	✓ 64-66	✓ 158-160
28	131		161 added
29-30	Merged with 131	67-68	162-163
	132 (separated from 131)	69	164
31-33	133-135	70	Merged with 164
34	Deleted	71-74	165-168
35	136	75-77	Deleted
36	137	78	169
37	Merged into 137	79	Merged with 169
38	138	80-82	170-172
✓ 39-41	✓ 139-141	83	Deleted

AMENDMENT A, Contd.

09/967,106	AMENDMENT A	09/967,106	AMENDMENT A
84	173	96-98	182-184
85	174	99	Deleted
86-87	Merged with 174	100	185
	175 (separated from 174)	101	186
88	176	102-103	Merged with 186
89-90	177-178		187 (separated from 186)
91	Deleted	104-106	188-190
92	179	107	Deleted
93	180	108	191
94-95	Merged with 180	109	192
	181 (separated from 180)		

✓

A GUIDE TO GO THROUGH THE CLAIMS IN AMENDMENT A:

Applicant also provides the following breakdown of the claims to go through the claims easily:

5 **1) Claims with fan-out of at most two in the first stage:**

Claims 110-115: 3-stage network.

Claims 116-117: Key method.

Claims 118-125: Detailed steps method.

Claims 126-130: Key method in a generic network.

10

2) Claims with fan-out of at most three in the first stage:

Claims 131-136: 3-stage network.

Claims 137-138: Key method.

AMENDMENT A, Contd.

Claims 139-144: Detailed steps method.

Claims 145-149: Key method in a generic network.

3) Claims with fan-out of at most any x (≥ 2) in the first stage:

5 Claims 150-155: 3-stage network.

Claims 156-157: Key method.

Claims 158-163: Detailed steps method.

Claims 164-168: Key method in a generic network.

10 **4) Claims with fan-out of arbitrary mix of at most any x (≥ 2) in the first stage:**

Claims 169-173: 3-stage network.

5) Claims with fan-out of at most two in the first stage:

Claims 174-179: 3-stage network for a subset of output switches.

15

6) Claims with fan-out of at most three in the first stage:

Claims 180-185: 3-stage network for a subset of output switches.

7) Claims with fan-out of at most any x (≥ 2) in the first stage:

20 Claims 186-191: 3-stage network for a subset of output switches.